

DEFINITION

Packaging Tape

TECHNICAL INFORMATION

No Noisy Adhesive Tape

DESCRIPTION	RULES	TYPE	UNIT of Meas.	VALUE	TOLERANCE %
Backing		BOPP			
Type of adhesive		Aqueous acrylic emulsion			
Total thickness			micron (µm)	47,0	± 10 %
Adhesion to steel	UNI EN ISO 1939		N/cm	≥ 2.0	
Rolling ball tack	PSTC 6		cm	≤ 8	
Shear	AFERA 5012		hr.	≥ 100	
Colours		Clear, Havana, White			

CUSTOMISATION

Not available

DIMENSIONS

Roll sizes :

Widht : 12 - 15 - 19 - 25 - 38 mm.

Lenght : 66 mtl

APPLICATION

The adhesive tape is applied manual onto a dry, clean surface (free from all traces of oil, grease or solvents), at a temperature of between 18 and 35 C°. Once applied, the product must not display any blisters or folds.

APPLICATION & STORAGE

Keep in a dry place, sheltered from the light, at a temperature of between 15° C and 25°C. The adhesive tapes must be kept and stored in the original packaging.

If storage conditions are not optimal, recondition the product before using it.

The adhesive tape must be applied within 6 months of date of shipment.

GENERAL WARRANTY TERMS

Product tests must be carried out on the surface actually used and must reproduce accurately all the finished product processing and storage conditions.

The values quoted are average values obtained from tests performed on standard production items and are not legally binding.

The values given in this technical data sheet are the outcome of analyses conducted on freshly manufactured items.

The technical characteristics of the adhesive tape may undergo changes over time without affecting product quality.

Naster shall not be liable for damages due to improper use of its material,

The warranty is limited to the replacement of the product in which manufacturing defects are ascertained by the Naster laboratory.

The product covers a wide range of use, however it is necessary to verify the application ,the surface on which to adhere and its cleaning .



ISSUED : LA Approved : GQ

Ed : 1 date : 08.02.2011 Rev : 0 Date